



## Directory of Listed Products



[Go to Directory Page](#)

### **BUILDING PRODUCTS LISTING PROGRAM**

**Class:** Concrete Roof Tiles

**Customer:** Boral Roofing

**Location:** 7575 Irvine Center Drive, Suite 100  
Irvine, CA 92618

**Website:** [www.boralamerica.com](http://www.boralamerica.com)

**Listing No.:** B1044-2

**Effective Date:** Mar 29, 2012

**Last Revised:** January 16, 2015

**Expires:** N/A

**Standards:** CSA A220 "Concrete Roof Tiles"  
ASTM E108 "Standard Test Methods for Fire Tests of Roof Coverings".  
CAN/ULC S107 "Standard Methods of Fire Tests of Roof Coverings".

**Product:** Concrete Roof Tiles

**Label:** Products are palletized and marked with a label that lists the Boral Roofing names which are US Tile and Monier Lefitile, Tile Profile, Plant Location and Address, SAP Number, Color Description, Quantity of tiles per pallet, Production date, Crew name and shift time, Logo of Certification Agency (CQAIUS), QAI Certification Listing Number (B1044-2) and the wording "CSA A220", "ASTM E108, Class A".

**Models:**

	<b>Saxony 900</b>	<b>Saxony 800</b>	<b>Villa 800</b>
<b>Length, inches</b>	17 ± 0.25	17 ± 0.25	17 ± 0.25
<b>Width, inches</b>	13 (-0.25/ +0.125)	13 ± 0.25	13 ± 0.25
<b>Height, inches</b>	1.156 ±0.125 Slate 1.281 ± 0.125 Shake	1.141 ±0.125 Slate 1.188 ±0.125 Shake	2 ±0.125
<b>Mass, pounds</b>	10.9 lbs ± 0.54 lbs	9.3 lbs ± 0.50 lbs	9 lbs ± 0.45 lbs
	<b>Villa 900</b>	<b>Barcelona 900</b>	<b>Ridge</b>
<b>Length, inches</b>	17 ± 0.25	17 ± 0.25	16.875 ± 0.125
<b>Width, inches</b>	13 ± 0.125	13 ± 0.125	10.5 ± 0.125
<b>Height, inches</b>	2.125 ± 0.094	2.125 ± 0.094	2.875 ± 0.125
<b>Mass, pounds</b>	9.7 lbs ± 0.1 lbs	9.7 lbs ± 0.1 lbs	7.65 lbs ± 0.25 lbs
	<b>Rake</b>	<b>Capri</b>	<b>Saxony Shake</b>
<b>Length, inches</b>	16.875 ± 0.125	16.875 ± 0.109	16.5 ± 0.25
<b>Width, inches</b>	8.25 ± 0.125	Nose side 9.875 ± 0.031 Head side 9.125 ± 0.031	13 ± 0.125
<b>Height, inches</b>	4.125 ± 0.125	Head Height 3.25 ± 0.125 Nose Height 4.063 ± 0.125	1.25 ± 0.047
<b>Mass, pounds</b>	8.45 lbs ± 0.25 lbs	7.20 lbs ± 0.36 lbs	11.25 lbs ± 0.55lbs
	<b>Saxony Slate</b>		
<b>Length, inches</b>	16.5 ± 0.25		
<b>Width, inches</b>	13 ± 0.125		
<b>Height, inches</b>	1.188 ± 0.047"		
<b>Mass, pounds</b>	11.25 lbs ± 0.55 lbs		

#### **ASTM E108 and CAN/ULC S107 Assembly**

##### **Class A Roofing Applications/No Slope Limitation**

<b>SHEATHING</b>	<b>UNDERLAYMENT</b>	<b>ROOF COVERING(s)</b>
		Saxony 900 Saxony 800 Villa 800

Minimum ½" Nominal Exposure 1 Plywood	1 Layer Type 30 ASTM D2261	Villa 900 Barcelona 900 Capri Saxony Shake Saxony Slate
--	-------------------------------	---

Note 1: Underlayment components are to be installed with mechanical fasteners in accordance with the manufacturer's published installation instructions. Self-adhering or adhesive applied underlayments are outside the scope of this listing.

**Note:** These products are subjected to limitations as specified above and must be installed in accordance with the manufacturers' instructions. Authorities having jurisdiction should be consulted regarding allowable applications. Final acceptance of the product as installed on a building is subject to approval by the authority having jurisdiction.

---

The materials, products or systems listed in this directory have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.

No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.

Visit the QAI Online Listing Directory located at [www.qai.org](http://www.qai.org) for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to [info@qai.org](mailto:info@qai.org). Please include the listing number in the request.

Copyright QAI Laboratories, 2015